



Jiya Fire Protection

AN ISO 9001:2015 CERTIFIED COMPANY

Head Office : Prathmesh Society, Sai Baba Gokul Nagar, Kranti Nagar, Akurli Road, Lokhandwala, Kandivali (E), Mumbai - 400 101.

Contact No.: 9648503737 / 9833166909

Email: jiya.fireprotection@gmail.com

GSTIN: 27CMGPP3334Q1ZF





ABOUT US

Jiya Fire services is a company with a provenmtrack record in the fire safety, Consulting & supply industry. We have earned respect of our customers by always Delivering quality advice, products and dependable service. our long standing Experience and individual care always allows us to be in tune with our customers Demands and needs; by taking care to always listen to our clients, we can continue to Provide a personal, high quality service that can be relied upon. our attention to detail guarantees your peace of mind.

OUR SERVICES

- Fire Extinguisher Installation & AMC
- Installations Of Fire Alarm & AMC
- Installations Of Fire Hydrant & AMC
- Installation Fire Water Tank
- Installation Fire Door

MAJOR CLIENTS



















ABC DRY POWDER ABC STORED PRESSURE SQUEEZE GRIP TYPE

Suitable For Classes Of Fire

Class A Fire: Wood Textile, Paper, Cloths, Cotton Mil, Jute Mill Etc.

Class B Fire: Petroleum, Oil Diesel, Paint, Varnish, Solvent, Aviation Fuel, Flammable And Volatile Liquids Etc.

Class C Fire: Flammable Gasses, Live Electrical Equipments, Industrial Gases, Electrical Installation, Power Grid Etc.

Available Capacity in Kgs.	1	2	4	6	9
IS Specification	15683	15683	15683	15683	15683
Test Pressure	35 bar	35 bar	35 bar	35 bar	35 bar
Average Discharge Time (s)	8	11	15	20	25
Fire Rating	1A,8B	1A, 13B	2A, 21B	3A, 21B	3A, 55B











DRY CHEMICAL POWDER SQUEEZE GRIP CARTRIDGE TYPE FIRE EXTINGUISHER

Suitable For Classes Of Fire

Class B Fire: Petroleum, Oil Diesel, Paint, Varnish, Solvent, Aviation Fuel, Flammable And Volatile Liquids Etc.

Class C Fire: Flammable Gasses, Live Electrical Equipments, Industrial Gases, Electrical Installation, Power Grid Etc.

Available Capacity in Kgs.	4	6	9
IS Specification	15683	15683	15683
Test Pressure	35 bar	35 bar	35 bar
Average Discharge Time (s)	15	20	25
Fire Rating	55B	89B	144B













CARBON DI OXIDE SQUEEZE GRIP & WHEEL TYPE FIRE EXTINGUISHER

Class B Fire: Petroleum, Oil Diesel, Paint, Varnish, Solvent, Aviation Fuel, Flammable And Volatile Liquids Etc. Class C Fire: Flammable Gasses, Live Electrical Equipments, Industrial Gases, Electrical Installation, Power Grid Etc.

Available Capacity in Kgs.	2	3	4.5
IS Specification	15683	15683	15683
Test Pressure	250 bar	250 bar	250 bar
Average Discharge Time (s)	9 sec	9 sec	10 sec
Fire Rating	8B	13B	34B











WATER STORED PRESSURE TYPE & SQUEEZE GRIP CARTRIDGE TYPE FIRE EXTINGUISHER

Suitable For Classes Of Fire

Class A Fire: Wood Textile, Paper, Cloths, Cotton Mil, Jute Mill Etc.

Caution: Not to use on live electrical equipment and water susceptible chemicals.

Available Capacity in Kgs.	6	9
IS Specification	15683	15683
Test Pressure	35 bar	35 bar
Average Discharge Time (s)	20	25
Fire Rating	2A	3A











CLEAN AGENT CLEAN AGENT FIRE EXTINGUISHER

Suitable For Classes Of Fire

Class A Fire: Wood Textile, Paper, Cloths, Cotton Mil, Jute Mill Etc.

Class B Fire: Petroleum, Oil Diesel, Paint, Varnish, Solvent, Aviation Fuel, Flammable And Volatile Liquids Etc.

Class C Fire: Flammable Gasses, Live Electrical Equipments, Industrial Gases, Electrical Installation, Power Grid Etc.

Available Capacity in Kgs.	2	4	6
IS Specification	15683	15683	15683
Test Pressure	35 bar	35 bar	35 bar
Average Discharge Time (s)	11	15	20
Fire Rating	1A, 13B	2A, 21B	3A, 21B











SAFETY SIGNAGES











A V SAFE FOR:













In case of fire


































Danger Steep ladders





HYDRANT SYSTEMS











































GUJARAT KOLKATA LUCKNOW NOIDA ...

